



Rigidex® HD5050UA

Product Technical Information

Rigidex® HD5050UA is a linear copolymer polyethylene grade supplied in pellet form for injection moulding application.

Typical applications

- Used in blend to improve stiffness

Benefits and Features

- Improved stiffness
- UV stabilized
- Whiteness

Properties		Test Methods	Values	Units
Physical				
Density		ISO 1872	950	kg/m ³
Melt Flow Rate	2.16 kg load	ISO 1133	4	g/10min
Mechanical				
Tensile Strength @ Yield (23°C Type 2 Speed D)		ISO 527	25	MPa
Elongation @ Break (23°C Type 2 Speed D)		ISO 527	> 1000	%
Flexural Modulus (23°C)		ISO 178	900	MPa
Charpy Impact Strength, 23°C		ISO 179	8	kJ/m ²
Hardness shore (D)		ISO 868	64	-
Thermal				
Melting point		ASTM D 2117	130	°C
Vicat softening point (A)		ISO 306	121	°C
Thermal conductivity		ASTM C 177	0.48	W/m ²
Specific heat		-	2300	J/kg °C
Coefficient of linear expansion		ASTM D 696	2x10 ⁻⁴	°C ⁻¹

- Data should not be used for specification work



Rigidex® HD5050UA

Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, send an email to psnohreg@ineos.com. Unless specifically indicated, the products mentioned herein are not suitable for applications in the medical or pharmaceutical sector.

Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Material Safety Data Sheet (MSDS) that may be obtained from the website www.ineospolyolefins.com. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

Exclusion of Liability

Although INEOS O&P Europe endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS O&P Europe is accurate and up to date, no representation or warranty, express or implied is made by INEOS O&P Europe as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS O&P Europe are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS O&P Europe materials are suitable for the particular purpose intended and INEOS O&P Europe shall not be responsible for any loss or damage caused by misuse of INEOS O&P Europe products. To the maximum extent permitted by law, INEOS O&P Europe accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS O&P Europe materials or the use of INEOS O&P Europe materials in conjunction with such other materials.