



Takht-e-Jamshid Pars Assalouyeh

Petrochemical Company

General Purpose Polystyrene ( GPPS )		
TYPICAL DATA SHEET	GRADE	<a href="http://www.tjpa-pc.com">www.tjpa-pc.com</a>
	TJPS-G1551 (Normal flow)	IRAN/ASSALOUYEH/PETROCHEMICAL COMPANY/ TEL : 077-37324159

This grade is normal flow polystyrene designed for extrusion or injection applications.

Main Applications:

Housewares , containers , toys , office stationary , etc.

#### TECHNICAL SPECIFICATION

PROPERTIES	UNIT	VALUE	STANDARD
Tensile Strength (Yield)	(kg/cm <sup>2</sup> )	450	D-638
Tensile Modulus of Elasticity	(kg/cm <sup>2</sup> )	2.6×10 <sup>4</sup>	D-638
Izod Impact Strength (notched,t=6.4 mm)	(kg-cm/cm )	2.1	D-256
Vicat Softening Point(1000 g)	(°C)	98	D-1525
Melt Index (200°C , 5000 g)	(g/10 min)	10	D-1238

\*All above mentioned data are typical values and not to be construed as real specifications. Users should confirm results by their own tests. Which is included MFI and Vicat.

\*\* TJPAPC Guaranteed items are MFI and Vicat .

Site : Next to Styrene park, Outset of  
Phase II Petrochemical Zone  
ASSALOUYEH , IRAN  
Tel : +98 (77) 3732 4161  
Fax : +98 (77) 3732 4079

Head Office : No. 12, second floor,  
Gandhi 14<sup>th</sup> str. , Valiasr Ave.  
TEHRAN, IRAN  
Tel : +98 (21) 8819 5919  
Fax : +98 (21) 8829 5719

[www.tjpa-pc.com](http://www.tjpa-pc.com)

[info@tjpa-pc.com](mailto:info@tjpa-pc.com)